

ATF II-D



PRODUCT DESCRIPTION

Oscar ATF II - D is multipurpose automatic transmission fluid for use in automatic gear boxes and power steering systems of vehicles where Dexron II D is recommended.

APPLICATION

For most passenger cars, forklift trucks and buses of European, American or Japanese origin. It is also suitable for certain power steering systems, torque converters, change-gearboxes, fluid clutches and non-complicated hydraulic systems.

PROPERTIES

- Low pour point for easy shifting at cold starts
- Seals are not affected by this ATF
- Maintains its lubricity without losing the high quality even at high temperatures

PERFORMANCE LEVELS

Meets and exceeds:

GM DEXRON II D, Allison C-4, Ford WSS-M2C166-H, MAN Type Z1/V1, MB 236.1

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Oscar ATF II-D
Density @ 15°C	ASTM D1298	kg/l	0.870
Viscosity @ 100°C	ASTM D445	cSt	7.0
Viscosity @ 40°C	ASTM D445	cSt	37
Viscosity Index (min)	ASTM D2270	-	≥160
Brookfield Viscosity @-40 °C	ASTM D2983	cP	<50,000
Pour Point	ASTM D97	°C	-44
Flash Point	ASTM D92	°C	210

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com